



Industrial 200kw Diesel Generator Ricardo Genset 1500RPM / 1800RPM

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO9001
- Model Number: DE-W275
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: 200kw Diesel Generator
- Engine Brand: Ricardo
- Cooling Method: Water-Cooling System
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **Industrial 200kw Diesel Generator,
200kw Diesel Generator 1800RPM,
Ricardo Genset 1500RPM**

for more products please visit us on dellentpower.com

CE Ricardos Diesel Generator about 200kW

At our Ricardos generator dealership, we understand the importance of quality and reliability when it comes to power generation. That's why we only offer the best generators from Ricardos, a leading manufacturer of power equipment.

. PRODUCT

		50 Hz				60 Hz				TECHNICAL DATA				RICARDO				WATER-COOLED Series Diesel Generator Sets			
		Genset Performance				Engine Performance				Dimension(L x W x H)											
	Genset Model	Prime Power		Standby Power		Engine model	Speed	Prime power	Fuel Cons. (100% Load)	Cylinder Bore-Stroke	Displace-ment	Open Type		Silent Type							
		kW	kVA	kW	kVA							mm	mm	mm	mm						
5000	DE-W22	16	20	18	22	4YT23-20D	1500	20	≤240	4 88×95	2.31	130×78×96	220×93×123								
	DE-W27	20	25	22	27	N4100DS-30	1500	30	≤225	4 100×115	3.61	130×78×96	220×93×123								
	DE-W33	24	30	26	33	N4100DS-30	1500	30	≤225	4 100×115	3.61	130×78×96	220×93×123								
	DE-W41	30	38	33	41	N4105DS-38	1500	38	≤220	4 105×120	4.15	130×78×96	220×93×123								
	DE-W55	40	50	44	55	N4105ZDS	1500	56	≤210	4 105×120	4.15	153×78×115	230×93×123								
	DE-W66	48	60	53	66	N4105ZDS	1500	56	≤210	4 105×120	4.15	159×78×115	239×93×123								
	DE-W74	54	68	59	74	N4105ZLDS	1500	66	≤210	4 105×120	4.15	159×85×121	239×98×128								
	DE-W96	70	88	77	96	R6105ZDS	1500	84	≤220	6 105×125	6.49	186×90×121	285×108×160								
	DE-W96	70	88	77	96	4RT55-88D	1500	88	≤205	4 110×140	5.32	178×85×121	260×108×150								
	DE-W110	80	100	88	110	R6105ZLDS	1500	100	≤218	6 105×125	6.49	186×90×121	285×108×160								
6000	DE-W110	80	100	88	110	4RT55-88D	1500	88	≤205	4 110×140	5.32	186×90×121	280×105×150								
	DE-W132	96	120	106	132	4RT55-110D	1500	110	≤205	4 110×140	5.32	186×90×121	280×105×150								
	DE-W138	100	125	110	138	R6105AZLDS	1500	121	≤218	6 105×130	6.75	235×103×160	300×110×150								
	DE-W165	120	150	132	165	R6105BZLDS	1500	132	≤218	6 105×135	7.01	235×103×160	315×120×162								
	DE-W165	120	150	132	165	6RT80-132D	1500	132	≤205	6 110×140	7.98	235×103×160	315×120×162								
	DE-W220	160	200	176	220	6RT80-176DE	1500	176	≤205	6 110×140	7.98	273×105×172	340×130×185								
	DE-W275	200	250	220	275	WT10B-231DE	1500	231	≤205	6 126×130	10.09	279×105×172	380×130×200								
	DE-W344	250	313	275	344	WT13B-308DE	1500	308	≤205	6 131×155	12.53	279×105×172	400×135×210								
	DE-W413	300	375	330	413	WT13B-330DE	1500	330	≤205	6 131×155	12.53	279×105×172	400×135×210								
8000	DE-W18	13	16	14	18	4YT23-20D	1800	22	≤240	4 88×95	2.31	130×78×96	220×93×123								
	DE-W25	18	23	20	25	N4100DS-30	1800	33	≤225	4 100×115	3.61	130×78×96	220×93×123								
	DE-W31	22	28	24	31	N4100DS-30	1800	33	≤225	4 100×115	3.61	130×78×96	220×93×123								
	DE-W37	27	33	30	37	N4100DS-30	1800	33	≤220	4 100×115	3.61	130×78×96	220×93×123								
	DE-W47	34	43	37	47	N4105DS-38	1800	41.8	≤210	4 105×120	4.15	130×78×96	230×93×123								
	DE-W55	40	50	44	55	N4100ZDS-42	1800	46.2	≤210	4 105×120	4.15	130×78×96	239×93×123								
	DE-W69	50	63	55	69	N4105ZDS	1800	61.6	≤210	4 105×120	4.15	153×78×115	239×96×128								
	DE-W83	60	75	66	83	N4105ZLDS	1800	72.6	≤220	4 105×120	4.15	159×78×115	285×108×160								
	DE-W91	66	83	73	91	4RT55-88D	1800	96.8	≤205	4 110×140	5.32	159×85×121	260×108×150								
	DE-W106	77	96	85	106	R6105ZDS	1800	92.4	≤218	6 105×125	6.49	186×90×121	285×108×160								
10000	DE-W110	80	100	88	110	4RT55-88D	1800	96.8	≤205	4 110×140	5.32	178×85×121	280×105×150								
	DE-W124	90	113	99	124	R6105ZLDS	1800	110	≤205	6 105×125	6.49	186×90×121	290×105×150								
	DE-W124	90	113	99	124	4RT55-110D	1800	121	≤218	4 110×140	5.32	186×90×121	280×105×150								
	DE-W138	100	125	110	138	4RT55-110D	1800	121	≤218	4 110×140	5.32	186×90×121	280×105×150								
	DE-W151	110	138	121	151	R6105AZLDS	1800	133.1	≤205	6 105×130	6.75	235×103×160	315×120×162								
	DE-W179	130	163	143	179	R6105BZLDS	1800	145.2	≤205	6 105×135	7.01	235×103×160	315×120×162								
	DE-W179	130	163	143	179	6RT80-132D	1800	145.2	≤205	6 110×140	7.98	235×103×160	305×130×185								
	DE-W220	160	200	176	220	6RT80-176DE	1800	193.6	≤205	6 110×140	7.98	273×105×172	340×130×185								

. Why Choose Us:

Dedicated

We are DEDICATED to meet Customers' need.

Enthusiasm

We respond to our Customers' ENTHUSIASM

Loyalty

We cherish our Customers' LOYALTY

Luxury

We aim to establish our own LUXURY brand

Efficient

We offer our EFFICIENT service

Newest

We adopt NEWEST technologies for products

Trust

We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



FAQ

Q: What's your delivery time?

A: Standard product 20 days - 30 days.

Q: Can we add our logo to products?

A: Yes, there are several ways to do this. We can put the label of your logo on the products or make the silk print of your logo on the products. It is free.

Q: Can we customize the product?

A: We have a very experienced technical team, we can customize any product according to your requirements, such as synchronization system, wet exhaust system, ultra-silent system



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDECITY,FUJIAN.CHINA