Water Cooled 600 Kw Perkins Generator Set DE-P825 12 Months Warranty

Basic Information

Place of Origin: CHINA
Brand Name: DELLENT
Certification: CE/ISO9001
Model Number: DE-P825
Minimum Order Quantity: 1 PC

Price: bargain face-to-face

Packaging Details: PLASTIC WRAP OR PLYWOOD CASE

Delivery Time: 20-30 DAYSPayment Terms: L/C, T/T

• Supply Ability: 1 MONTH 600PCS



Product Specification

Name: 600 Kw Perkins Generator

• Engine Brand: Perkins

Cooling Method: Water-Cooling System

Fuel Type: DieselRated Frequency: 50HZ/60HZ

Speed: 1500RPM/1800RPMWarranty: 12 Months/1000 Hours

Highlight: Water Cooled 600 Kw Perkins Generator,

600 Kw Perkins Generator Set, 600kw Water Cooled Generator Set

CE Perkins Diesel Generator about 600kW

Looking for reliable Perkins generators for your power needs? Look no further than ourPerkins generator dealership! We are proud to offer a wide range of high-quality Perkins gensets that are perfect for both residential and commercial use. Don't settle for less when it comes to your power needs. Choose aPerkins generator from our dealership today and experience the power and reliability that only Perkins can offer. Contact us to learn more about ourPerkins generators and services. Perkins generator with international Warranty Service

_	-						PF	-R	KINS	3			
2	0 60 Hz TECHNICAL DATA						WATER-COOLED Series Diesel Generator Sets						
							Engine Performance					Dimension(L×W×H)	
	Senset Model	Prime Power		Standby Power		Engine model	Speed		Fuel Cons.	Cylinder-	Displace	Open Type	Silent Type
								power	(100% Load)	Bore*Stroke	Displace -ment		SHOTE TYPE
	DE-P10	7.2	VVA:	a.	10	403D-11G	1500	8.6	2.6	3L-77×81	1.131	115×74×99	180×84×110
	DE-P10	10	12.5	11	14	403A-15G1	1500	12.2	3.7	3L-84×90	1,496	115×74×99	180×84×110
	DE-P17	12	15	13.2	16.5	403A-15G2	1500	14	5	3L-84×90	1.496	115×74×99	180×84×110
	DE-P22	16	20	17.6	22	404A-22G1	1500	18.7	5.3	4L-84×100	2.216	127×74×101	180×84×110
	DE-P30	22	27.5	24	30	404D-22TG	1500	25.2	7.1	4L-84×100	2.216	136×74×101	180×84×110
	DE-P33	24	30	26.4	33	1103A-33G	1500	28.2	7.2	3L-105×127	3.3	152×80×122	230×102×128
	DE-P50	36	45	40	50	1103A-33TG1	1500	42.2	10.8	3L-105×127	3.3	161×80×122	230×102×128
	DE-P66	48	60	52.8	66	1103A-33TG2	1500	55	14.6	3L-105×127	3.3	169×80×122	230×102×128
	DE-P72	52	65	57.6	72	1104A-44TG1	1500	59.6	14.6	4L-105×127	4.4	181×80×124	240×102×128
	DE-P88	64	80	70.4	88	1104A-44TG2	1500	73.4	18.7	4L-105×127	4.4	185×80×124	240×102×128
	DE-P110	80	100	88	110	1104C-44TAG2	1500	93.6	22.6	4L-105×127	4.41	188×85×124	272×108×170
	DE-P150 DE-P165	108	135	120	165	1106A-70TG1 1106A-70TAG2	1500	122.7	30.2	6L-105×135 6L-105×135	7.01	224×90×141 224×90×141	330×110×170 330×110×170
	DE-P165 DE-P200	144	180	160	200		1500	163.9	41.6	6L-105×135	7.01	224×90×141 230×90×141	340×110×170
	DE-P200	160	200	176	220	1106A-70TAG3 1106A-70TAG4	1500	178.9	45.8	6L-105×135	7.01	235×90×141	340×110×170
	DE-P250	180	225	200	250	1506A-E88TAG2	1500	204	51	6L-112×149	8.8	262×110×162	360=130×190
	DE-P275	200	250	220	275	1506A-E88TAG3	1500	222	56	6L-112×149	8.8	262×110×162	360×130×190
	DE-P300	220	275	240	300	1506A-E88TAG4	1500	244	60	6L-112×149	8.8	273×110×162	380×130×190
	DE-P330	240	300	264	330	1506A-E88TAG5	1500	267	65	6L-112×149	8.8	273×110×162	380 * 130 × 190
	DE-P385	280	350	308	385	2206C-E13TAG2	1500	324	75	6L-130×157	12.5	299×120×185	420×140×223
	DE-P450	320	400	360	450	2206C-E13TAG3	1500	368	85	6L-130×157	12,5	308×120×185	430×140×223
	DE-P500	360	450	400	500	2506C-E15TAG1	1500	412	99	6L-137×171	15.2	345×120×198	470×160×223
	DE-P550	400	500	440	550	2506C-E15TAG2	1500	451	106	6L-137×171	15.2	345×120×198	470×160×223
	DE-P660	480	600	528	560	2806C-E18TAG1A	1500	532	129	6L-145×183	18.1	335×154×202	500×180×253
	DE-P720	520	650	576	720	2806A-E18TAG2	1500	584	132	6L-145×183	18.1	341×154×202	500×180×253
	DE-P825	600	750 800	660 704	825	4006-23TAG2A	1500	658 705	157	6L-160×190	22.921	402×171×221	580×200×253
	DE-P880 DE-P1000	728	900	800	1000	4006-23TAG3A 4008TAG1A	1500	805	195	6L-160×190 8L-160×190	30.561	402×171×221 470×205×235	580×200×253 680×228×256
	DE-P1000	820	1025	900	1125	4008TAG2A	1500	899	215	8L-160×190	30.561	470×205×235	680×228×256
	DE-P1375	1000	1250	1100	1375	4012-46TWG2A	1500	1113	259	12V-160×190	45 842	485×205×252	000-220-200
	DE-P1650	1200	1500	1320	1650	4012-46TAG2A	1500	1331	310	12V-160×190	45.842	485×205×252	40 feet high
	DE-P1875	1360	1700	1500	1875	4012-46TAG3A	1500	1500	370	12V-160×190	45.842	497×205×252	container
	DE-P2000	1480	1850	1600	2000	4016-61TRG1	1500	1648	371	16V-160×190	61.123	634×220×268	- 1
	DE-P2200	1600	2000	1760	2200	4016-61TRG2	1500	1774	405	16V-160×190	61.123	624×220×268	V
	DE-P2500	1800	2250	2000	2500	4016-61TRG3	1500	1975	470	16V-160×190	61.123	625×220×268	N.
	DE-P13	9	11.25	10	12.5	403D-11G	1800	10.7	3	3L-77×81	1.131	115×74×99	180×84×110
	DE-P17	12	15	13.2	16.5	403D-11G	1800	14.7	4 27	3184×90	1.496	115×74×99	180×84×110
	DE-P20	14.4	18	16	20	403A-15G2	1800	16	5	3L-84×90	1.496	115×74×99	180×84×110
	DE-P28	20	25	22	27.5	404D-22G	1800	22	6.2	4L-84×100	2.216	127×74×101	180×84×110
	DE-P33	24	30	26.4	33	404D-22TG	1800	30.3	8.3	4L-84×100	2.216	136×74×101	180 * 84 * 1100
	DE-P39	28	35	30.8	38.5	1103A-33G	1800	33.2	8.6	3L-105×127	3.3	152×80×122	230×102×128
	DE-P60	43	54	48	60	1103A-33TG1	1800	50.5	12.9	3L-105×127	3.3	161×80×122	230×102×128
	DE-P75	54	67.5	60	75	1103A-33TG2	1800	63.3	16.6	3L-105×127	3.3	169×80×122	230×102×128
	DE-P83	60	75	66	82.5	1104A-44TG1	1800	70.7	17.7	4L-105×127	4.4	181×80×124	240×102×128
	DE-P103	75	93.75	82.5	103	1104A-44TG2	1800	84.5	22.3	4L-105×127	4.4	185×80×124	240×102×128
	DE-P125	90	112.5	100	125	1104C-44TAG2	1800	106.8	26.9	4L-105×127	4.41	188×85×124	272×108×170
	DE-P165	120	150	132	165	1106A-70TG1	1800	140.5	35.2	8L-105×135	7.01	224×90×141	330×110×170
	DE-P188 DE-P220	135	169	150	187.5	1106A-70TAG2 1106A-70TAG3	1800	155 180.5	38.2 46.4	6L-105×135 6L-105×135	7.01	224×90×141 230×90×141	330×110×170 340×110×170
	DE-P220 DE-P270	160	200	176 216	270	1106A-70TAG3 1506A-E88TAG2	1800	180.5	46.4	6L-105×135 6L-112×149	8.8	230×90×141 262×110×162	340×110×170 360×130×190
	DE-P310	225	281	248	310	1506A-E88TAG2	1800	250	63	6L-112×149	8.8	262*110*162	360×130×190
	DE-P385	280	350	308	385	1506A-E88TAG5	1800	300	77	6L-112×149	8.8	273×110×162	380×130×190
	DE-P440	320	400	352	440	2206A-E13TAG2	1800	373	81	6L-13D×157	12.5	299×120×185	420×140×223
	DE-P550	400	500	440	550	2506C-E15TAG1	1800	453	106	6L-137×171	15.2	345×120×198	470×160×223
	DE-P688	500	625	550	687.5	2806C-E18TAG1A	1800	568	130	6L-145×183	18.1	335×154×202	500×180×253
	DE-P825	600	750	660	825	4006-23TAG2A	1800	684	177	6L-160×190	22.921	402×171×221	580×200×253
	DE-P935	680	850	748	935	4006-23TAG3A	1800	759	200	6L-160×190	22.921	402×171×221	580×200×253
	DE-P1100	800	1000	880	1100	4008TA G2	1800	898	224	8L-160×190	30.561	470×205×235	680×228×256
	DE-P1375	1000	1250	1100	1375	4012-46TWG2A	1800	1113	266	12V-160+190	45.842	485×205×252	40 feet high
	DE-P1650	1200	1500	1320	1650	4012-46TAG2A 4012-46TAG3A	1800	1332	319	12V-160×190 12V-160×190	45.842 45.842	485×205×252	container
	DE-P1875		1700	1500	1875				361			497×205×252	

. Why Choose Us:



We are DEDICATED to meet Customers' need.

We respond to our Customers' ENTHUSIASM

We cherish our Customers' LOYALTY

We aim to establish our own LUXURY brand

fficient

We offer our EFFICIENT service

ewest

We adopt NEWEST technologies for products

We strive for winning the TRUST from Customers

. QUALIFICATION CENTIFICATE:



















FACTORY INTERIOR:















Fuan Dellent Electric & Machinery Co., Ltd.









