DELLENT 138kva Perkins Diesel Generator Set Low Noise 1106A-70TG1 Engine

Basic Information

Place of Origin: CHINA
Brand Name: Ricardo
Certification: CE/ISO9001
Model Number: DE-P150
Minimum Order Quantity: 1*20GP
Price: face to face

Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
 Delivery Time: 30 DAYS FROM DEPOSIT RECEIVED

Payment Terms: L/C, T/T

• Supply Ability: 500 PCS PER MONTH



Product Specification

Name: 238kva Perkins Diesel Generator

• Brand: Perkins

• Type: Diesel Generator

• Alternator: STAMFORD And So On

Controller: Smartgen DSE

Cooling System: WaterFrequency: 50/60Hz

• Voltage: 380V Or As Your Request

• Warranty: One Year

PRODUCT DESCRIPTION

DELLENT 138kva Perkins Diesel Generator Set Low Noise 1106A-70TG1 Engine



Generator Set Specification

| denerator det opcombation | | | | |
|---------------------------|-----|---------|--|--|
| Model | | DE-P150 | | |
| | kVA | 108 | | |
| Max. Power | kW | 135 | | |
| Rate Power | kVA | 120 | | |
| | kW | 150 | | |
| Frequency | Hz | 50 | | |
| Rate Voltage | V | 400/230 | | |
| Rate Current | А | 194.86 | | |

Engine Specification

| Engine Brand | Perkins |
|-----------------|--------------------------------------------|
| Engine Model | 1106A-70TG1 |
| No. of Cylinder | 6 Cylinder in line |
| Aspiration | Turbocharged and Air to Air Aftercooled |
| Governor | Electric |

| Engine Max. Output Power | kW | 122.7 |
|-------------------------------|--------|----------|
| Displacement | L | 7.01 |
| Compression Ratio | · | 15.8 : 1 |
| Starting Voltage | V | 24 |
| Bore | mm | 105 |
| Stroke | mm | 135 |
| Lubrication Oil Capacity | L | 13-16 |
| Intake Air Flow | M3/Min | 16.4 |
| Fuel Consumption at 100% Load | L/H | 56.9 |

| Alternator Specification | | |
|--------------------------------------------|--------------------------------------------------------------------------------|--------------------------------|
| Alternator Manufacturer | | Cummins Generator Technologies |
| Alternator Brand | | Stamford |
| Rate Output | kVA | 138 |
| Frequency | Hz | 50Hz |
| Altitude | М | ≤1000 |
| Insulation | | Class H |
| Phase | | 3 Phase |
| Working Temperature without power decrease | | ≤40 |
| Working Altitude without power decrease | | ≤1000m |
| Automatic Voltage Regulation | | SX440 |
| Protection Grade | | IP23 |
| Alternator for optional | Leroy Somer, Marathon, Mecc Alte and DELLENT Brushless alternator for optional | |

FAQ

Question:

What's your delivery time?

Answer:

Our delivery time is 30 days after receiving your deposit

Question:

What's your warranty?

Answer:

We provide 1 year or 1000 hours warranty to our industrial and marine generator

Question:

Do you provide OEM or ODM service?

Yes, in DELLENT FACTORY, we have R&D department which professional in resolving any tailored needs of our Customers, OEM and ODM are available.



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com